

WILKERSON FRL'S CB6 COMPACT FILTER/REGULATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/09/2026 02:56 AM

SKU
: 26190

BRAND
: DIXON VALVE

MODEL
: CB6-03MG

Applications:

Over-under units are space savers and provide for installation in tight areas. One common inlet/outlet for both filter and regulator saves on piping costs.

Use:

Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Features:

- Manual Drain
- Transparent Bowl and Guard
- 0-125 PSIG adjusting range
- 5 micron reusable element
- 5 oz. bowl
- Self-relieving standard
- Diaphragm operated
- Quick-disconnect bowl guard with integral plastic bowl and safety latch standard
- Supplied with a GC230 gauge

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	CB6-03MG
Flow	70.0 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	2.5400