

CJ-SERIES PNEUMATIC MALE THREADED PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/22/2026 08:42 AM

SKU

: 10102

BRAND

: DIXON VALVE

MODEL

: CJ2BM2-LG

Specifications:

Rated pressure for connected Brass Coupler & Steel Plug: 300 PSI (20 bar)

Maximum Working and 9,500 PSI (655 bar) Burst

Construction:

Machined components are manufactured using solid steel bar stock.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

European High-Flow Interchange

Interchanges with CEJN 320, Coilhouse Megaflow, Rectus 25KA/26KA and other like designs

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	CJ2BM2-LG
Hex	9/16"
Length	1.48" (37.5mm)
Material	Steel
Maximum OD	0.65" (16.5mm)
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	BSPT
Thread Size	1/4"
Weight Lb	0.0700