

CJ-SERIES PNEUMATIC MALE THREADED PLUG



DATE
: 07/09/2026 10:30 PM

SKU
: 10109

BRAND
: DIXON VALVE

MODEL
: CJ2M2-B

Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 bar)
Maximum Working and 7,200 PSI (500 bar) Burst

Construction:

Machined components are manufactured using solid brass bar stock.

Compatibility & Interchange Data:


European High-Flow Interchange

Interchanges with CEJN 320, Coilhouse Megaflo, Rectus 25KA/26KA and other like designs

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	CJ2M2-B
Hex	9/16"
Length	1.48" (37.5mm)
Material	Brass
Maximum OD	0.65" (16.5mm)
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	1/4"
Weight Lb	0.0500