

## CJ-SERIES PNEUMATIC MALE THREADED PLUG



DATE  
: 07/09/2026 10:30 PM

SKU  
: 10111

BRAND  
: DIXON VALVE

MODEL  
: CJ2M3-B

### Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 bar)  
Maximum Working and 7,200 PSI (500 bar) Burst

### Construction:

Machined components are manufactured using solid brass bar stock.

### Compatibility & Interchange Data:


European High-Flow Interchange

Interchanges with CEJN 320, Coilhouse Megaflo, Rectus 25KA/26KA and other like designs

### Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/4"
<b>Factory Part Number</b>	CJ2M3-B
<b>Hex</b>	11/16"
<b>Length</b>	1.56" (39.5mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	0.79" (20.1mm)
<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	NPT
<b>Thread Size</b>	3/8"
<b>Weight Lb</b>	0.0800