

CJ-SERIES PNEUMATIC FEMALE THREADED PLUG



DATE
: 07/09/2026 09:33 PM

SKU
: 10115

BRAND
: DIXON VALVE

MODEL
: CJ3BF4

Specifications:

Rated pressure for connected Brass Coupler & Steel Plug: 300 PSI (20 bar)
Maximum Working and 8,000 PSI (552 bar) Burst

Construction:

Machined components are manufactured using solid steel bar stock.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.


Compatibility & Interchange Data:

European High-Flow Interchange
Interchanges with Rectus 27KA, CEJN 410 and other like designs

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Factory Part Number	CJ3BF4
Hex	1"
Length	1.71" (43.5mm)
Material	Steel
Maximum OD	1.16" (29.5mm)
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	BSPP
Thread Size	1/2"
Weight Lb	0.2000