


CJ-SERIES PNEUMATIC FEMALE THREADED PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 09:34 PM

SKU

: 10122

BRAND

: DIXON VALVE

MODEL

: CJ3F3-B

Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 bar)

Maximum Working and 4,400 PSI (300 bar) Burst

Construction:

Machined components are manufactured using solid brass bar stock.

Compatibility & Interchange Data:

European High-Flow Interchange

Interchanges with Rectus 27KA, CEJN 410 and other like designs

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Factory Part Number	CJ3F3-B
Hex	7/8"
Length	1.50" (38.0mm)
Material	Brass
Maximum OD	1.01" (25.7mm)

TECHNICAL SPECIFICATIONS

Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	3/8"
Weight Lb	0.1700