

**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE PLUG
MALE NPTF**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 06:58 AM

SKU
: 10147

BRAND
: DIXON VALVE

MODEL
: CM2M1-B

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 10,000 PSI (700 bar) Burst
Rated pressure for connected Brass Valved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 6,000 PSI (400 bar) Burst

Construction:

Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:

Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	CM2M1-B
Hex	9/16"
Length	1.00"
Material	Brass
Maximum OD	0.65"
Temperature Range	-90°F to +400°F (-68°C to +205°C)

TECHNICAL SPECIFICATIONS

Thread	Male NPTF
Thread Size	1/8"-27
Weight Lb	0.0200