

**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE
EXTENSION PLUG**



DATE
: 07/08/2026 04:34 PM

SKU
: 10149

BRAND
: DIXON VALVE

MODEL
: CM2M1-B-L4

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 10,000 PSI (700 bar) Burst
Rated pressure for connected Brass Valved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 6,000 PSI (400 bar) Burst

Construction:

Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:

Mold Coolant Interchange

Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	CM2M1-B-L4
Hex	7/16"
Length	4.00"
Material	Brass
Maximum OD	0.51"
Temperature Range	-90°F to +400°F (-68°C to +205°C)

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Thread	Male NPTF
Thread Size	1/8"-27
Weight Lb	0.1000