

**DQC CM-SERIES INDUSTRIAL  
MOLD INTERCHANGE PLUG  
FEMALE NPTF**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/22/2026 06:59 AM

SKU  
: 10157

BRAND  
: DIXON VALVE

MODEL  
: CM3F2

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 14,200 PSI (1,000 bar) Burst  
Rated pressure for connected Brass Valved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 6,100 PSI (400 bar) Burst

Construction:

Machined components are manufactured using solid bar stock  
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

Mold Coolant Interchange  
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	3/8"
<b>Factory Part Number</b>	CM3F2
<b>Hex</b>	5/8"
<b>Length</b>	1.34"
<b>Material</b>	Steel
<b>Maximum OD</b>	0.72"

## TECHNICAL SPECIFICATIONS

<b>Temperature Range</b>	-90°F to +400°F (-68°C to +205°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1/4"-18
<b>Weight Lb</b>	0.0550