

**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE PLUG
FEMALE NPTF**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 06:59 AM

SKU
: 10159

BRAND
: DIXON VALVE

MODEL
: CM3F3

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 14,200 PSI (1,000 bar) Burst
Rated pressure for connected Brass Valved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 6,100 PSI (400 bar) Burst

Construction:

Machined components are manufactured using solid bar stock
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Factory Part Number	CM3F3
Hex	3/4"
Length	1.34"
Material	Steel
Maximum OD	0.87"

TECHNICAL SPECIFICATIONS

Temperature Range	-90°F to +400°F (-68°C to +205°C)
Thread	Female NPTF
Thread Size	3/8"-18
Weight Lb	0.0600