

**DQC CM-SERIES INDUSTRIAL  
MOLD INTERCHANGE  
EXTENSION PLUG**



DATE  
: 07/08/2026 04:36 PM

SKU  
: 10162

BRAND  
: DIXON VALVE

MODEL  
: CM3M1-B-L4



Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 14,500 PSI (1,000 bar) Burst  
Rated pressure for connected Brass Valved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 6,700 PSI (450 bar) Burst

Construction:

Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:

Mold Coolant Interchange  
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

|                            |                                   |
|----------------------------|-----------------------------------|
| <b>Body Size</b>           | 3/8"                              |
| <b>Factory Part Number</b> | CM3M1-B-L4                        |
| <b>Hex</b>                 | 9/16"                             |
| <b>Length</b>              | 4.00"                             |
| <b>Material</b>            | Brass                             |
| <b>Maximum OD</b>          | 0.65" (16.5mm)                    |
| <b>Temperature Range</b>   | -90°F to +400°F (-68°C to +205°C) |

**TECHNICAL SPECIFICATIONS**

|                    |           |
|--------------------|-----------|
| <b>Thread</b>      | Male NPTF |
| <b>Thread Size</b> | 1/8"-27   |
| <b>Weight Lb</b>   | 0.1000    |