

**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE PLUG
MALE NPTF**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 05:43 PM

SKU
: 10165

BRAND
: DIXON VALVE

MODEL
: CM3M2-B

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 14,500 PSI (1,000 bar) Burst
Rated pressure for connected Brass Valved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 6,700 PSI (450 bar) Burst

Construction:

Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:

Mold Coolant Interchange

Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|-----------------------------------|
| Body Size | 3/8" |
| Factory Part Number | CM3M2-B |
| Hex | 9/16" |
| Length | 1.37" |
| Material | Brass |
| Maximum OD | 0.65" |
| Temperature Range | -90°F to +400°F (-68°C to +205°C) |

TECHNICAL SPECIFICATIONS

| | |
|--------------------|-----------|
| Thread | Male NPTF |
| Thread Size | 1/4"-18 |
| Weight Lb | 0.0500 |