

**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE PLUG
FEMALE NPTF**



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 05:42 PM

SKU
: 10174

BRAND
: DIXON VALVE

MODEL
: CM4F4-B

Specifications:
Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

Construction:
Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:
Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:
Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|-----------------------------------|
| Body Size | 1/2" |
| Factory Part Number | CM4F4-B |
| Hex | 1" |
| Length | 1.69" |
| Material | Brass |
| Maximum OD | 1.16" |
| Temperature Range | -90°F to +400°F (-68°C to +205°C) |
| Thread | Female NPTF |

TECHNICAL SPECIFICATIONS

| | |
|--------------------|---------|
| Thread Size | 1/2"-14 |
| Weight Lb | 0.1100 |