


**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE PLUG
FEMALE NPTF**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 06:58 AM

SKU
: 10174

BRAND
: DIXON VALVE

MODEL
: CM4F4-B

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

Construction:

Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:

Mold Coolant Interchange

Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	CM4F4-B
Hex	1"
Length	1.69"
Material	Brass
Maximum OD	1.16"
Temperature Range	-90°F to +400°F (-68°C to +205°C)
Thread	Female NPTF

TECHNICAL SPECIFICATIONS

Thread Size	1/2"-14
Weight Lb	0.1100