


**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE PLUG
FEMALE NPTF**



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 05:42 PM

SKU
: 10175

BRAND
: DIXON VALVE

MODEL
: CM4F6-B

Specifications:
Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

Construction:
Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:
Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:
Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	CM4F6-B
Hex	1-3/16"
Length	1.69"
Material	Brass
Maximum OD	1.37" (34.8mm)
Temperature Range	-90°F to +400°F (-68°C to +205°C)
Thread	Female NPTF

TECHNICAL SPECIFICATIONS

Thread Size	3/4"-14
Weight Lb	0.1000