

**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE PLUG
MALE NPTF**



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 05:43 PM

SKU
: 10177

BRAND
: DIXON VALVE

MODEL
: CM4M6-B

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

Construction:

Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:

Mold Coolant Interchange

Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	CM4M6-B
Hex	1-1/16"
Length	1.79"
Material	Brass
Maximum OD	1.23"
Temperature Range	-90°F to +400°F (-68°C to +205°C)
Thread	Male NPTF

TECHNICAL SPECIFICATIONS

Thread Size	3/4"-14
Weight Lb	0.2000