

## DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 11:49 PM

SKU

: 10359

BRAND

: DIXON VALVE

MODEL

: CVV2BF2

Construction:

Machined components are manufactured using solid bar stock

Steel retaining rings and springs maximize service life in rugged environments.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Nipples have a PTFE Anti-Extrusion ring to prevent O-Ring damage during dynamic impulse service.

Compatibility & Interchange Data:

European Screw-Together Interchange

Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS,

Stucchi VD Series

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/4"
<b>Burst Pressure</b>	26000 PSI (1800 Bar)
<b>Factory Part Number</b>	CVV2BF2
<b>Hex</b>	19mm
<b>Length</b>	2.36" (60.0mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	0.94" (24.0mm)
<b>Maximum Operating Pressure</b>	6500 PSI (450 Bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)

**TECHNICAL SPECIFICATIONS**

<b>Thread</b>	Female BSPP
<b>Thread Size</b>	1/4"-19