

DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 11:54 PM

SKU
: 10366

BRAND
: DIXON VALVE

MODEL
: CVV3FM1615

Construction:

Machined components are manufactured using solid bar stock

Steel retaining rings and springs maximize service life in rugged environments.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Nipples have a PTFE Anti-Extrusion ring to prevent O-Ring damage during dynamic impulse service.

Compatibility & Interchange Data:

European Screw-Together Interchange

Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	26000 PSI (1800 Bar)
Factory Part Number	CVV3FM1615
Hex	22mm
Length	2.52" (64.0mm)
Material	Steel
Maximum OD	1.10" (28.0mm)
Maximum Operating Pressure	6500 PSI (450 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)

TECHNICAL SPECIFICATIONS

Thread Female Metric

Thread Size M16X1.5