

DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE PLUG



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 01:10 PM

SKU
: 10371

BRAND
: DIXON VALVE

MODEL
: CVV4FM2215

Construction:
Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nipples have a PTFE Anti-Extrusion ring to prevent O-Ring damage during dynamic impulse service.

Compatibility & Interchange Data:
European Screw-Together Interchange
Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 1" |
| Burst Pressure | 23200 PSI (1600 Bar) |
| Factory Part Number | CVV4FM2215 |
| Hex | 41mm |
| Length | 3.94" (70.0mm) |
| Material | Steel |
| Maximum OD | 1.89" (36.0mm) |
| Maximum Operating Pressure | 5800 PSI (400 Bar) |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |

TECHNICAL SPECIFICATIONS

| | |
|--------------------|---------------|
| Thread | Female Metric |
| Thread Size | 1" - 11-1/2 |
| Weight Lb | 0.7000 |