

**DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE PLUG**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 11:50 PM

SKU  
: 10377

BRAND  
: DIXON VALVE

MODEL  
: CVV6FM2215

**Construction:**

Machined components are manufactured using solid bar stock

Steel retaining rings and springs maximize service life in rugged environments.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Nipples have a PTFE Anti-Extrusion ring to prevent O-Ring damage during dynamic impulse service.

**Compatibility & Interchange Data:**

European Screw-Together Interchange

Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS,

Stucchi VD Series

**Safety notes:**

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	3/4"
<b>Burst Pressure</b>	23200 PSI (1600 Bar)
<b>Factory Part Number</b>	CVV6FM2215
<b>Hex</b>	36mm
<b>Length</b>	3.39" (86.0mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	1.65" (42.0mm)
<b>Maximum Operating Pressure</b>	5800 PSI (400 Bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)

**TECHNICAL SPECIFICATIONS**

<b>Thread</b>	Female Metric
<b>Thread Size</b>	M22X1.5
<b>Weight Lb</b>	1.2600