

DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE PLUG



DATE
: 05/22/2026 12:57 PM

SKU
: 10380

BRAND
: DIXON VALVE

MODEL
: CVV8F8

Construction:

Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nipples have a PTFE Anti-Extrusion ring to prevent O-Ring damage during dynamic impulse service.

Compatibility & Interchange Data:


European Screw-Together Interchange
Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1"
Burst Pressure	17600 PSI (1200 Bar)
Factory Part Number	CVV8F8
Hex	41mm
Length	3.94" (100.0mm)
Material	Steel
Maximum OD	1.89" (48.0mm)
Maximum Operating Pressure	4400 PSI (300 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Thread	Female NPTF
Thread Size	1" - 11-1/2
Weight Lb	1.6000