

**DQC H-SERIES ISO-B FOOD
GRADE NYLON FLANGED
FEMALE THREADED COUPLER**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 11:28 AM

SKU

: 23766

BRAND

: DIXON VALVE

MODEL

: D-4HF4-S-FNS

Features:

Poppet style shut-off valves

Designed to prevent fluid loss when disconnected

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Nylon flanged sleeve

FDA FKM seals are standard

Redundant o-ring sealing system with PTFE backup ring

Valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.

Available Options:

Contact Dixon for all available option adders

Compatibility & Interchange Data:

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	27500 PSI (1900 bar)
Factory Part Number	D-4HF4-S-FNS
Hex	1-1/16"
Length	2.86" (72.6mm)
Material	303 Stainless Steel
Maximum OD	2.38" (60.5mm)
Maximum Operating Pressure	3500 PSI (240 bar)
Temperature Range	-40°F to +400°F (-40°C to +204°C)
Thread	Female NPTF
Thread Size	1/2"-14
Weight Lb	0.8400