

BAYLOC® DRY DISCONNECT ADAPTER X FEMALE NPT

DATE
: 07/08/2026 01:51 AM

SKU
: 11296

BRAND
: DIXON VALVE

MODEL
: DBA12-150

Applications:

Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss. For use in transfer of hazardous fluids

Use:

Use with DBC or D2C style couplers
Use with standard cam and groove dust caps sized one size larger than the dry disconnect size
Use Cam & Groove Dust Cap Size: 2"

Features:

Two-piece adapter design for easy rebuilding of adapters

Compatibility & Interchange Data:

Compatible with most other brands of cam and groove style dry disconnects
Fully interchangeable with Kamvalok (OPW trademark) style fittings

Note:

Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

Safety notes:

For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Adapter Size	2"
Description	Cam & Groove Style
Factory Part Number	DBA12-150
Female Thread	NPT
Female Thread Size	1-1/2"
Material	Zinc/Aluminum
Maximum Operating Pressure	210 PSI at 70°F(21°C)
Seal	FKM
Weight Lb	2.0000