

BAYLOC® DRY DISCONNECT ADAPTER X FEMALE NPT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability



DATE
: 04/15/2026 09:38 PM

SKU
: 11320

BRAND
: DIXON VALVE

MODEL
: DBA74-200

Applications:

Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss. For use in transfer of hazardous fluids

Use:

Use with DBC or D2C style couplers
Use with standard cam and groove dust caps sized one size larger than the dry disconnect size
Use Cam & Groove Dust Cap Size: 2-1/2"

Features:

Two-piece adapter design for easy rebuilding of adapters

Construction:

Stainless steel piston
Stainless steel corrosion resistance is comparable to 304 stainless steel

Compatibility & Interchange Data:

Compatible with most other brands of cam and groove style dry disconnects
Fully interchangeable with Kamvalok (OPW trademark) style fittings

Note:

Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

Safety notes:

For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Adapter Size	2-1/2"
Description	Cam & Groove Style
Factory Part Number	DBA74-200
Female Thread	NPT
Female Thread Size	2"
Material	Stainless Steel
Maximum Operating Pressure	150 PSI at 70°F(21°C)
Seal	EPDM
Weight Lb	4.6000