

## BAYLOC® DRY DISCONNECT ADAPTER X FEMALE NPT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability



DATE

: 07/08/2026 04:08 AM

SKU

: 11325

BRAND

: DIXON VALVE

MODEL

: DBA77-150

### Applications:

Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss. For use in transfer of hazardous fluids

### Use:

Use with DBC or D2C style couplers

Use with standard cam and groove dust caps sized one size larger than the dry disconnect size

Use Cam & Groove Dust Cap Size: 2"

### Features:

Two-piece adapter design for easy rebuilding of adapters

### Construction:

Stainless steel piston

Stainless steel corrosion resistance is comparable to 304 stainless steel

### Compatibility & Interchange Data:

Compatible with most other brands of cam and groove style dry disconnects

Fully interchangeable with Kamvalok (OPW trademark) style fittings

### Note:

Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

### Safety notes:

For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Adapter Size</b>	2"
<b>Description</b>	Cam & Groove Style
<b>Factory Part Number</b>	DBA77-150
<b>Female Thread</b>	NPT
<b>Female Thread Size</b>	1-1/2"
<b>Material</b>	Stainless Steel
<b>Maximum Operating Pressure</b>	210 PSI at 70°F(21°C)
<b>Seal</b>	PTFE Encapsulated FKM
<b>Weight Lb</b>	3.6000