

BAYLOC® DRY DISCONNECT ADAPTER X 150# ASA FLANGE

DATE
: 04/21/2026 03:47 AM

SKU
: 27416

BRAND
: DIXON VALVE

MODEL
: DBAF71-300



** Referential image*

*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:

Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss.

Use:

Use with DBC or D2C style couplers

Use with standard cam and groove dust caps sized one size larger than the dry disconnect size

Use Cam & Groove Dust Cap Size: 4"

Construction:

Stainless steel piston

Stainless steel corrosion resistance is comparable to 304 stainless steel

Compatibility & Interchange Data:

Compatible with most other brands of cam and groove style dry disconnects

Fully interchangeable with Kamvalok (OPW trademark) style fittings

Note:

Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

Safety notes:

For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Adapter Size	4"
Description	Cam & Groove Style
Flange Size	3"
Material	Stainless Steel
Maximum Operating Pressure	120 PSI at 70°F(21°C)
Factory Part Number	DBAF71-300
Seal	Buna
Weight Lb	18.2600