

## BAYLOC® DRY DISCONNECT ADAPTER X 150# ASA FLANGE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 01:51 AM

SKU

: 11335

BRAND

: DIXON VALVE

MODEL

: DBAF74-200

### Applications:

Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss. For use in transfer of hazardous fluids

### Use:

Use with DBC or D2C style couplers

Use with standard cam and groove dust caps sized one size larger than the dry disconnect size

Use Cam & Groove Dust Cap Size: 2-1/2"

### Construction:

Stainless steel piston

Stainless steel corrosion resistance is comparable to 304 stainless steel

### Compatibility & Interchange Data:

Compatible with most other brands of cam and groove style dry disconnects

Fully interchangeable with Kamvalok (OPW trademark) style fittings

### Note:

Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

### Safety notes:

For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Adapter Size</b>	2-1/2"
<b>Description</b>	Cam & Groove Style
<b>Factory Part Number</b>	DBAF74-200
<b>Flange Size</b>	2"
<b>Material</b>	Stainless Steel
<b>Maximum Operating Pressure</b>	150 PSI at 70°F(21°C)
<b>Seal</b>	EPDM
<b>Weight Lb</b>	0.0100