

BAYLOC® DRY DISCONNECT COUPLER X FEMALE NPT

DATE

: 07/08/2026 04:43 AM

SKU

: 11354

BRAND

: DIXON VALVE

MODEL

: DBC66-300

Applications

Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss.

Use

Use with DBA style adapters

Use with standard cam and groove dust plug sized one size larger than the dry disconnect size

Use Cam & Groove Dust Plug Size: 2-1/2"

Specifications

Canadian registration number CRN # OH14044 all provinces

Features

Coupler has automatic closing poppet assembly

Heavy duty construction provides long service life

Stainless steel handle allows product exposure to corrosive chemicals or washdown service

Strong handle attachment prevents bending of crank assembly

Large paddle type cam arms are standard on 3" fittings, allow for an easy grip

Optional coupler lock for handle to prevent unintentional opening

Construction


Stainless steel internals

Heavy duty stainless steel handle, crank and link

FFKM gasket, main seal O-ring and handle O-ring, PTFE seals on cylinder assembly, stuffing box and seal under poppet screw

Compatibility & Interchange Data

Compatible with most other brands of cam and groove style dry disconnects



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

Note

Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

Safety notes

Must be used with a DBA (Dry Break Cam & Groove) Style adapter for coupler to operate. Adapter sold separately.

For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------|
| Coupler Size | 4" |
| Description | Cam & Groove Style |
| Factory Part Number | DBC66-300 |
| Female Thread | NPT |
| Female Thread Size | 3" |
| Material | Aluminum |
| Maximum Operating Pressure | 120 PSI at 70°F(21°C) |
| Seal | FFKM & PTFE |
| Weight Lb | 0.0100 |