

DF-SERIES CARTRIDGE ELEMENTS- PES MEMBRANE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability



DATE
: 04/29/2026 01:39 AM

SKU
: 11643

BRAND
: DIXON VALVE

MODEL
: DF-PESF7E4S

Specifications:

Maximum differential pressure: 45 PSID

Maximum operating pressure: 45 PSID

Cartridge Element Lengths: 10" to 40"

Micron ratings: .1, .22, .45, .60, .80, 1.2 and 5.0

Features:

FDA title 21 compliant

Cartridge elements are constructed in a clean room environment

Cartridge elements have excellent dirt holding capacity with low flow resistance

Cartridge elements are free of surfactants, resins, binders, and adhesives

Low protein binding and chemical compatibility

Naturally hydrophilic media does not need wetting before use

Construction:

Cartridge element: polyethersulfone; core material: polypropylene

Gasket/O-Ring: Buna, FKM, PTFE, silicone, neoprene, and EPDM

Note:

All sizes are 6pcs/case and sold in case quantities only.

There are many more options, including industrial housing and cartridge elements. All cartridge elements are manufactured to industry standards and are interchangeable with other manufacturers' products. Please call Dixon Sanitary 800.789.1718 for further information.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Cartridge Element Length	30"
Case	Case Qty: 6 pieces
Diameter	2.65" OD/ 1" Center ID
Material	Polyethersulfone/Polypropylene/Silicone
Micron Rating	.45
Factory Part Number	DF-PESF7E4S
Style	Hard Cage/222/Closed