

## DF-SERIES CARTRIDGE ELEMENTS- HIGH EFFICIENCY PLEATED



DATE  
: 04/28/2026 11:59 PM

SKU  
: 11654

BRAND  
: DIXON VALVE

MODEL  
: DF-PHEBK34S

Specifications:

Retention rating of 99.98%

Recommended change out differential pressure: 35 PSID (2.4 bar)

Cartridge Element Lengths: 9.75" to 40"

Micron ratings: .2, .45, 1, 3, 5, 10, 25, and 50

Available in hard charge (standard) or netted cage

Features:

FDA title 21 compliant

Cartridge elements are constructed in a clean room environment

Cartridge elements are free of surfactants, resins, binders, and adhesives

Construction:

Cartridge element: polypropylene

Gasket/O-Ring: Buna, FKM, PTFE, silicone, neoprene, and EPDM

Note:

All sizes are 6pcs/case and sold in case quantities only.

There are many more options, including industrial housing and cartridge elements. All cartridge elements are manufactured to industry standards and are interchangeable with other manufacturers' products. Please call Dixon Sanitary 800.789.1718 for further information.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Cartridge Element Length</b>	10"
<b>Case</b>	Case Qty: 6 pieces
<b>Diameter</b>	2.65"
<b>Material</b>	Polypropylene, Silicone
<b>Micron Rating</b>	1
<b>Factory Part Number</b>	DF-PHEBK34S
<b>Style</b>	Hard Cage/222/Closed
<b>Weight Lb</b>	5.0000