

MANNTEK DRY GAS ADAPTER TANK UNIT X FEMALE NPT

DATE
: 07/09/2026 02:00 PM

SKU
: 11700

BRAND
: DIXON VALVE

MODEL
: DGA100SS



Applications:

Dry gas couplings are designed for safe loading and discharge of bobtails or intermediate bulk delivery trucks and transfer to and from railcars.

The primary application is in the handling of LPG- Propane and Butane.

Features:

Quick and easy to connect and can be connected to a hose unit with pressures up to 225 PSI

For higher pressure, couplings can easily be equipped with a pressure relief valve that dissipates trapped fluid pressure into the hose coupler without spillage.

Reliable- easy to use, easy to maintain and saves time

Minimizes the risk of cold burns, spillage and product loss, and health risks

Keeps the environment free of hazardous vapors and liquids

Construction:

Stainless steel and brass/gunmetal

Gunmetal is produced to U.S. government bronze specification G

Compatibility & Interchange Data:

Compatible with existing dry disconnect couplings

Safety notes:

Working pressure is based on PSI at ambient temperature 70°F, for pressure ratings at other temperatures contact Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Body Size	56 mm
Factory Part Number	DGA100SS
Female Thread	NPT
Female Thread Size	1"
Material	316 Stainless Steel
Seal	FKM (FPM)
Weight Lb	1.7700
Working Pressure	360 PSI