

FUELER 100? PLUS

DATE

: 04/14/2026 08:08 PM

SKU

: 11922

BRAND

: DIXON VALVE

MODEL

: DNOG5PL

Applications

Designed for high-volume fuel transfer

Typical uses include high-volume truck fleet and bus terminals, fuel oil delivery, and industrial operations

Specifications

Inlet: 1-1/4" 1-1/2" NPT or BSPP

Spout: 1-3/8"

Weight: 6.9 lbs.

Length: 13.5"

Maximum working pressure: 100 PSI, 90 GPM

Features

Higher flow rate than standard fueling nozzles

High-strength aluminum body casting for great durability

Roto-matic latch pin for smooth automatic shut-off

PTFE stem packing eliminates leaks

Dual poppers for easy high-pressure operation

Grooved spout holds nozzle in the tank

Hand guard is integrated with the body

Nylon spout lock nut does not gall, making it easy to change the spout

Construction

Body: high-strength aluminum

Body cap: high-strength cast aluminum

Spout: aluminum

Lever: high-strength cast aluminum

Vacuum cap: zinc

Main stem: stainless steel

Seals: FKM/Nitrile

Packing: PTFE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

Safety notes

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	1-1/4" NPT inlet Hi-Flow PLUS fuel nozzle with 1-3/8 spout
Factory Part Number	DNOG5PL
Weight Lb	6.9000