

DQC E-SERIES STRAIGHT THROUGH INTERCHANGE HOSE BARB PLUG



DATE
: 07/09/2026 03:35 AM

SKU
: 23979

BRAND
: DIXON VALVE

MODEL
: E2S2



Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series

These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:

Machined components are manufactured using solid steel

Steel componentry is plated using ROHS Compliant Trivalent Chrome

Steel nipples are hardened to provide heavy duty performance.

Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Burst Pressure	22,000 PSI (1,517 Bar)
Factory Part Number	E2S2
Hose ID	1/4"
Length	1.90 (48.3mm)
Material	Steel
Maximum OD	0.56 (14.2mm)
Maximum Operating Pressure	5,500 PSI (379 Bar)
Weight Lb	0.0500