

## E74 SERIES 1 FRL'S STANDARD COMBINATION UNIT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 06:02 AM

SKU  
: 26214

BRAND  
: DIXON VALVE

MODEL  
: E74-4M

Applications:  
These units are intended for use in industrial compressed air systems only.

Features:  
Manual Drain  
Transparent Bowl and Guard  
7 oz. reservoir  
Supplied with a GC230 gauge  
Combination Units are supplied with micro-fog lubricators.  
Includes 2 clamps and wall mounting brackets # 4314-52, 2 clamps # 4314-51 and 2 NPT pipe adapters.  
Clean with warm water only.

Installation  
Connected modularly

Safety notes:  
FRL's are designed for air service only, unless otherwise indicated.  
The polycarbonate plastic bowls used on these units can be damaged and possibly burst if exposed to such substances as certain solvents, strong alkalis, compressor oils that contain ester-based additives or synthetic oils. Fumes of these substances in contact with polycarbonate bowl, externally and internally, can also result in damage.  
Use metal bowl in applications where a plastic bowl might be exposed to substances that are incompatible with polycarbonates.  
Clean plastic bowl is warm water only.  
SCFM ratings at 90 PSIG inlet pressure  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Manual Drain, Transparent Bowl and Guard
<b>Factory Part Number</b>	E74-4M
<b>Flow</b>	150 SCFM
<b>Includes</b>	With Gauge
<b>Inlet Pressure</b>	150 PSI
<b>Mandatory Pkg/Box Qty</b>	1
<b>Maximum Temperature</b>	125°F (51°C)
<b>Port</b>	1/2"
<b>Pressure Range</b>	5-150 PSI
<b>Weight Lb</b>	7.9000