

EZLINK? ARMLESS CAM & GROOVE TYPE C COUPLER X HOSE SHANK



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/14/2026 11:48 AM

SKU

: 12247

BRAND

: DIXON VALVE

MODEL

: EZL150-C-AL

Applications:

Transfer and/or unloading of fuels (gasoline or diesel) from tank truck to storage tanks

Transfer of liquids compatible with the available coupling and gasket materials

Features:

Automatic couplers push-to-connect providing a reliable connection

Low profile allows easy connection and disconnection in tight applications

Coupler push tabs can be locked with safety pins and/or zip tie

Compatible with standard cam and groove adapters

EZLink™ stainless steel tabs are guaranteed for life! Should you ever break one return it to the nearest warehouse for a free replacement.

Construction:

Couplings: A356 Aluminum

Coupler tabs and springs: 316 stainless steel

Gasket: Buna-N

Safety notes:

Only use EZLink™ gaskets and tabs for this coupling system. Traditional cam & groove handles and gaskets, or other types of seals are not compatible and will fail.

Warning: Failure to follow the recommended procedures may result in serious injury and property damage.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Material	A356 Aluminum
Maximum Operating Pressure	250 PSI (with King Crimp? Ferrules), 250 PSI (with Crimp Sleeves), 250 PSI (with Band Clamps)
Factory Part Number	EZL150-C-AL
Seal	Buna-N Gasket
Size	1 1/2"
Temperature Range	Gasket: 5°F to 180°F (-15°C to 82°C)
Weight Lb	0.6650