

## EZLINK? ARMLESS CAM & GROOVE TYPE C COUPLER X HOSE SHANK



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/14/2026 11:48 AM

SKU

: 12269

BRAND

: DIXON VALVE

MODEL

: EZL400-C-AL

### Applications:

Transfer and/or unloading of fuels (gasoline or diesel) from tank truck to storage tanks

Transfer of liquids compatible with the available coupling and gasket materials

### Features:

Automatic couplers push-to-connect providing a reliable connection

Low profile allows easy connection and disconnection in tight applications

Coupler push tabs can be locked with safety pins and/or zip tie

Compatible with standard cam and groove adapters

EZLink™ stainless steel tabs are guaranteed for life! Should you ever break one return it to the nearest warehouse for a free replacement.

### Construction:

Couplings: A356 Aluminum

Coupler tabs and springs: 316 stainless steel

Gasket: Buna-N

### Safety notes:

Only use EZLink™ gaskets and tabs for this coupling system. Traditional cam & groove handles and gaskets, or other types of seals are not compatible and will fail.

Warning: Failure to follow the recommended procedures may result in serious injury and property damage.

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Material</b>	A356 Aluminum
<b>Maximum Operating Pressure</b>	150 PSI (with King Crimp? Ferrules), 110 PSI (with Crimp Sleeves), 100 PSI (with Band Clamps)
<b>Factory Part Number</b>	EZL400-C-AL
<b>Seal</b>	Buna-N Gasket
<b>Size</b>	4"
<b>Temperature Range</b>	Gasket: 5°F to 180°F (-15°C to 82°C)
<b>Weight Lb</b>	2.2000