


DQC H-SERIES ISO-B FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/29/2026 04:45 PM

SKU

: 24014

BRAND

: DIXON VALVE

MODEL

: F-H2F2-B

Features:

Poppet style shut-off valves

Designed to prevent fluid loss when disconnected

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:

Contact Dixon for all available option adders

Oxy-Clean treatment is available

Compatibility & Interchange Data:

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	15000 PSI (1000 bar)
Hex	3/4"
Length	1.55" (39.4mm)
Material	Brass
Maximum OD	0.83" (21.1mm)
Maximum Operating Pressure	3000 PSI (200 bar)
Factory Part Number	F-H2F2-B
Seal	FKM
Temperature Range	-20°F to +400°F (-29°C to +204°C)
Thread	Female NPTF
Thread Size	1/4"-18
Weight Lb	0.0900