

DIXON SANITARY STYLE CRIMP FERRULE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 07:38 AM

SKU
: 24076

BRAND
: DIXON VALVE

MODEL
: F32G-3000

Applications:

Recommended for food, dairy and pharmaceutical applications where increased flow capacity is important.

Construction:

Ferrules have a surface finish of 63 or better

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

Holedall couplings, regardless of coupling style, are never to be used for steam service at any pressure.

Holedall fittings are not to be used with cable reinforced high-pressure hose, 4 or 6 braid wire hydraulic hose or any other service not listed in the recommendations. Consult Dixon for recommendations on usage.

For applications other than the ones list, please consult Dixon.

Hose service working pressure (including surges and spikes) is never to exceed the maximum recommended working pressure for the fitting. The assembly's (hose + coupling) maximum working pressure is the lesser of the hose rated working pressure or the coupling rated working pressure.

Media being transported through the hose should be compatible with the stem material. Compatibility of ferrule material with the environment in which it will be used is recommended. Consult the Compatibility Chart or the Dixon factory for material compatibility.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	F32G-3000
Hose ID	2"
Hose OD From	2-60/64" (2.971)
Hose OD To	2-63/64" (3.007)
Material	AISI 304 Stainless Steel
Weight Lb	0.8510