

## F74 SERIES 1 FRL'S OIL REMOVAL (COALESCING) FILTER



DATE  
: 07/08/2026 06:24 AM

SKU  
: 26346

BRAND  
: DIXON VALVE

MODEL  
: F74C-4A-MB

### Features:

- Automatic Drain
- Metal Bowl
- Quick-release bayonet bowl
- Prismatic lens liquid level indicator
- Provides air quality class 2 hydrocarbon and class 1 particulate removal per ISO 8573-1
- Element removes particles down to 0.01mm. Maximum remaining oil content of air leaving the filter is 0.01 ppm at 70°F (21°C) with an inlet concentration of 8 ppm
- Service life indicator turns from green to red when element needs to be replaced

### Installation

In-line or modular installation

### Note:

For maximum service life install a general purpose filter upstream of the oil removal filter.

### Safety notes:

- FRL's are designed for air service only, unless otherwise indicated.
- SCFM ratings at 90 PSIG inlet pressure
- WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

### TECHNICAL SPECIFICATIONS

<b>Description</b>	Standard Flow
<b>Factory Part Number</b>	F74C-4A-MB
<b>Flow</b>	75 SCFM Dry, 35 SCFM Saturated
<b>Inlet Pressure</b>	250 PSI at 150°F (66°C)
<b>Port</b>	1/2"
<b>Weight Lb</b>	1.9650