

F74 SERIES 1 FRL'S OIL REMOVAL (COALESCING) FILTER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/21/2026 11:51 AM

SKU

: 26346

BRAND

: DIXON VALVE

MODEL

: F74C-4A-MB

Features:

Automatic Drain

Metal Bowl

Quick-release bayonet bowl

Prismatic lens liquid level indicator

Provides air quality class 2 hydrocarbon and class 1 particulate removal per ISO 8573-1

Element removes particles down to 0.01mm. Maximum remaining oil content of air leaving the filter is 0.01 ppm at 70°F (21°C) with an inlet concentration of 8 ppm

Service life indicator turns from green to red when element needs to be replaced

Installation

In-line or modular installation

Note:

For maximum service life install a general purpose filter upstream of the oil removal filter.

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Standard Flow
Factory Part Number	F74C-4A-MB
Flow	75 SCFM Dry, 35 SCFM Saturated
Inlet Pressure	250 PSI at 150°F (66°C)
Port	1/2"
Weight Lb	1.9650