

F74 SERIES 1 FRL'S OIL REMOVAL (COALESCING) FILTER



DATE
: 04/21/2026 11:39 AM

SKU
: 26360

BRAND
: DIXON VALVE

MODEL
: F74H-6A-MB

Features:

- Automatic Drain
- Metal Bowl
- Quick-release bayonet bowl
- Prismatic lens liquid level indicator
- Provides air quality class 2 hydrocarbon and class 1 particulate removal per ISO 8573-1
- Element removes particles down to 0.01mm. Maximum remaining oil content of air leaving the filter is 0.01 ppm at 70°F (21°C) with an inlet concentration of 8 ppm
- Service life indicator turns from green to red when element needs to be replaced

Installation

In-line or modular installation

Note:

For maximum service life install a general purpose filter upstream of the oil removal filter.

Safety notes:

- FRL's are designed for air service only, unless otherwise indicated.
- SCFM ratings at 90 PSIG inlet pressure
- WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|---------------------------------|
| Description | High Flow |
| Factory Part Number | F74H-6A-MB |
| Flow | 120 SCFM Dry, 60 SCFM Saturated |
| Inlet Pressure | 250 PSI at 150°F (66°C) |
| Port | 3/4" |
| Weight Lb | 2.9000 |