

## F74 SERIES 1 FRL'S OIL REMOVAL (COALESCING) FILTER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 06:24 AM

SKU

: 26360

BRAND

: DIXON VALVE

MODEL

: F74H-6A-MB

Features:

Automatic Drain

Metal Bowl

Quick-release bayonet bowl

Prismatic lens liquid level indicator

Provides air quality class 2 hydrocarbon and class 1 particulate removal per ISO 8573-1

Element removes particles down to 0.01mm. Maximum remaining oil content of air leaving the filter is 0.01 ppm at 70°F (21°C) with an inlet concentration of 8 ppm

Service life indicator turns from green to red when element needs to be replaced

Installation

In-line or modular installation

Note:

For maximum service life install a general purpose filter upstream of the oil removal filter.

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	High Flow
<b>Factory Part Number</b>	F74H-6A-MB
<b>Flow</b>	120 SCFM Dry, 60 SCFM Saturated
<b>Inlet Pressure</b>	250 PSI at 150°F (66°C)
<b>Port</b>	3/4"
<b>Weight Lb</b>	2.9000