

FH-SERIES SANITARY FILTER HOUSINGS



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability



DATE

: 07/12/2026 11:14 PM

SKU

: 12457

BRAND

: DIXON VALVE

MODEL

: FH-12-30B30CS

Applications:

Used for separating solid matter from liquid in the food processing, beverage, dairy, wineries and breweries, personal care products, and chemical markets.

Specifications:

150 PSI working pressure at 300°F (149°C)

1-1/2" clamp vent/gauge connection standard

1/2" clamp drain connection standard

222 or 226 cartridge elements

Clamp connection sizes: 1"- 4"

Number of elements: 1, 3, 5, 7, 12, and 21

Cartridge element lengths: 10", 20" 30", and 40"

Features:

Utilizes a single bolt closure to ensure positive sealing

High purity construction assures dependable protection for critical process applications

Custom OEM designs available

Large variety of cartridge elements available to meet your application needs

Construction:

Product contact: 316L stainless steel

32Ra OD polish; 25Ra ID polish

Silicone O-ring seals standard; FKM and EPDM options

Available Options:

Different finishes

Variety of connections

Note:

Cartridge elements are not included with the filter housings and must be

ordered separately.

There are many more options, including industrial housings. Please call Dixon Sanitary 800.789.1718 for further information.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Cartridge Element Length	30"
Intended Service	Number of Elements: 12
Material	316L Stainless Steel
Factory Part Number	FH-12-30B30CS
Seal	Silicone O-Ring
Size	3" Clamp
Style	Element Type: 226