

FH-SERIES SANITARY FILTER HOUSINGS



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/30/2026 02:47 PM

SKU

: 12462

BRAND

: DIXON VALVE

MODEL

: FH-7-30A20CS

Applications:

Used for separating solid matter from liquid in the food processing, beverage, dairy, wineries and breweries, personal care products, and chemical markets.

Specifications:

150 PSI working pressure at 300°F (149°C)

1-1/2" clamp vent/gauge connection standard

1/2" clamp drain connection standard

222 or 226 cartridge elements

Clamp connection sizes: 1"- 4"

Number of elements: 1, 3, 5, 7, 12, and 21

Cartridge element lengths: 10", 20" 30", and 40"

Features:

Utilizes a single bolt closure to ensure positive sealing

High purity construction assures dependable protection for critical process applications

Custom OEM designs available

Large variety of cartridge elements available to meet your application needs

Construction:

Product contact: 316L stainless steel

32Ra OD polish; 25Ra ID polish

Silicone O-ring seals standard; FKM and EPDM options

Available Options:

Different finishes

Variety of connections

Note:

Cartridge elements are not included with the filter housings and must be

ordered separately.

There are many more options, including industrial housings. Please call Dixon Sanitary 800.789.1718 for further information.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|---------------------------------|-----------------------|
| Cartridge Element Length | 30" |
| Intended Service | Number of Elements: 7 |
| Material | 316L Stainless Steel |
| Factory Part Number | FH-7-30A20CS |
| Seal | Silicone O-Ring |
| Size | 2" Clamp |
| Style | Element Type: 222 |