

## ALUMINUM MALE X FEMALE SWIVEL BUTTERFLY VALVE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/09/2026 10:34 AM

SKU  
: 13525

BRAND  
: DIXON VALVE

MODEL  
: FMBTFLY40F40F

#### Applications:

This valve permits safe controlled flow to the intake pump and can be used in draft situations.

#### Use:

This unit can be used in either direction i.e.: inlet/outlet.

#### Features:

Hard anodized lightweight aluminum flanges provide a longer life span.

#### Construction:

Body wafer is lightweight aluminum cast 356-T6 with standard 10 position lever handle.

Comes furnished with a 3/4" push-pull drain valve.

Body of valve is ASTN A-126 cast iron

Buna seat

Finish hardcoat anodized cast aluminum bolt flanges- minimum thickness 0.001"

#### Note:

Lever handle to center valve is 10-1/4"

#### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Height</b>	18.0"
<b>Length</b>	9.5"
<b>Male Thread</b>	NST (NH)
<b>Male Thread Size</b>	4"
<b>Factory Part Number</b>	FMBTFLY40F40F
<b>Pressure Rating</b>	200 PSI
<b>Swivel Thread</b>	NST (NH)
<b>Swivel Thread Size</b>	4"
<b>Width</b>	11.0"