

ALUMINUM MALE X FEMALE SWIVEL BUTTERFLY VALVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/20/2026 04:34 PM

SKU

: 13527

BRAND

: DIXON VALVE

MODEL

: FMBTFLY40F60F

Applications:

This valve permits safe controlled flow to the intake pump and can be used in draft situations.

Use:

This unit can be used in either direction i.e.: inlet/outlet.

Features:

Hard anodized lightweight aluminum flanges provide a longer life span.

Construction:

Body wafer is lightweight aluminum cast 356-T6 with standard 10 position lever handle.

Comes furnished with a 3/4" push-pull drain valve.

Body of valve is ASTN A-126 cast iron

Buna seat

Finish hardcoat anodized cast aluminum bolt flanges- minimum thickness 0.001"

Note:

Lever handle to center valve is 10-1/4"

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Height	18.0"
Length	9.5"
Male Thread	NST (NH)
Male Thread Size	4"
Factory Part Number	FMBTFLY40F60F
Pressure Rating	185 PSI
Swivel Thread	NST (NH)
Swivel Thread Size	6"
Width	11.0"