

ALUMINUM MALE X FEMALE SWIVEL BUTTERFLY VALVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/20/2026 04:34 PM

SKU

: 13528

BRAND

: DIXON VALVE

MODEL

: FMBTFLY50F45F

Applications:

This valve permits safe controlled flow to the intake pump and can be used in draft situations.

Use:

This unit can be used in either direction i.e.: inlet/outlet.

Features:

Hard anodized lightweight aluminum flanges provide a longer life span.

Construction:

Body wafer is lightweight aluminum cast 356-T6 with standard 10 position lever handle.

Comes furnished with a 3/4" push-pull drain valve.

Body of valve is ASTN A-126 cast iron

Buna seat

Finish hardcoat anodized cast aluminum bolt flanges- minimum thickness 0.001"

Note:

Lever handle to center valve is 10-1/4"

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|---------------|
| Height | 18.0" |
| Length | 9.5" |
| Male Thread | NST (NH) |
| Male Thread Size | 5" |
| Factory Part Number | FMBTFLY50F45F |
| Pressure Rating | 185 PSI |
| Swivel Thread | NST (NH) |
| Swivel Thread Size | 4-1/2" |
| Width | 11.0" |