

ALUMINUM MALE X FEMALE SWIVEL BUTTERFLY VALVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/09/2026 10:34 AM

SKU
: 13528

BRAND
: DIXON VALVE

MODEL
: FMBTFLY50F45F

Applications:

This valve permits safe controlled flow to the intake pump and can be used in draft situations.

Use:

This unit can be used in either direction i.e.: inlet/outlet.

Features:

Hard anodized lightweight aluminum flanges provide a longer life span.

Construction:

Body wafer is lightweight aluminum cast 356-T6 with standard 10 position lever handle.

Comes furnished with a 3/4" push-pull drain valve.

Body of valve is ASTN A-126 cast iron

Buna seat

Finish hardcoat anodized cast aluminum bolt flanges- minimum thickness 0.001"

Note:

Lever handle to center valve is 10-1/4"

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Height	18.0"
Length	9.5"
Male Thread	NST (NH)
Male Thread Size	5"
Factory Part Number	FMBTFLY50F45F
Pressure Rating	185 PSI
Swivel Thread	NST (NH)
Swivel Thread Size	4-1/2"
Width	11.0"