

**PISTON INTAKE FEMALE
SWIVEL X MALE WITH RELIEF
VALVE**



DATE
: 04/24/2026 02:20 AM

SKU
: 13560

BRAND
: DIXON VALVE

MODEL
: FMGR45F40F

Applications:
Valve permits safe controlled flow to the intake pump and can also be used to draft.

Features:
Relief valve- double spring, cartridge type, adjustable from 50 to 200 PSI

Construction:
High strength aluminum alloy, 356-T6
Finish hardcoat anodized throughout- minimum thickness 0.001"
The valve is complete with a 30° elbow (permitting smoother water flow), adjustable relief valve, retractable knob on hand wheel and air bleed off.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Female Thread	NST (NH) swivel
Female Thread Size	(2) 4"
Height	17.0"
Length	12.0"
Male Thread	NST (NH)
Male Thread Size	4-1/2"
Material	Aluminum
Maximum Operating Pressure	280 PSI
Factory Part Number	FMGR45F40F

TECHNICAL SPECIFICATIONS

Width 8.0"