

**PISTON INTAKE FEMALE
SWIVEL X MALE WITH RELIEF
VALVE**



DATE
: 04/24/2026 02:21 AM

SKU
: 13565

BRAND
: DIXON VALVE

MODEL
: FMGR50F45F

Applications:
Valve permits safe controlled flow to the intake pump and can also be used to draft.

Features:
Relief valve- double spring, cartridge type, adjustable from 50 to 200 PSI

Construction:
High strength aluminum alloy, 356-T6
Finish hardcoat anodized throughout- minimum thickness 0.001"
The valve is complete with a 30° elbow (permitting smoother water flow), adjustable relief valve, retractable knob on hand wheel and air bleed off.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Female Thread	NST (NH) swivel
Female Thread Size	(2) 4-1/2"
Height	17.0"
Length	12.0"
Male Thread	NST (NH)
Male Thread Size	5"
Material	Aluminum
Maximum Operating Pressure	280 PSI
Factory Part Number	FMGR50F45F

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Width 8.0"